



www.asic-net.com

Commandor

Scale Master

Analog Indicator

TS-02



INDICATOR	DESCRIPTION
CPU	ARM Cortex 64 bits 1.4 GHz
Memory	1 GB SDRAM, 32 GB SD CARD
Display	TFT Resolution 1280x768 with Capacitive Touch Screen
Language	Multi-Language UNICODE Default THAI/ENGLISH
Signal Input	Analog 1-3 mV/V
Excitation Voltage	5 +/- 0.1 VDC
Analog To Digital	Delta-Sigma 24 Bits
Internal Resolution	100,000 Division
Clock & Calendar	Real Time Clock (RTC)
Loadcell	Up to 8 Loadcells
Decimal point	0 – 3 Digits
Serial Communication	Serial RS-232 1 x Printer, 1 x Remote display
USB	Keyboard, Mouse, Barcode Reader, Memory, Camera
Power Supply	16 VDC, 3 Amp.
Dimension (W x H x D)	30 x 20 x 11 cm.
Casing	Acrylic + Stainless Steel
PRINTER	DESCRIPTION
Method	Thermal
Interface	RS-232C
Character/Line	32 Char.
Font Code	English / Thai KU42
Barcode	3OF9 , QR-CODE

Specifications subject to change without notice

INDICATOR